

AD-A093 765

AEROSPACE CORP EL SEGUNDO CA SPACE SCIENCES LAB

F/G 4/1

VLF EMISSIONS FROM A MODULATED ELECTRON BEAM IN THE AURORAL ION--ETC(U)

NOV 80 R H HOLZWORTH, H C KOONS

F04701-80-C-0081

UNCLASSIFIED

TR-0081(6960-05)-1


SD-TR-80-77

NL

1-1
AD-A093 765



END
DATE
FILMED
2 81
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS 1963-A

PORT 82-77-80-77

LEVEL II

AD A093765

VLF Emissions from a Modulated Electron Beam in the Auroral Ionosphere

Prepared by R. H. HOLZWORTH and H. C. KOCH
Space Sciences Laboratory
Laboratory Operations
The Aerospace Corporation
El Segundo, Calif. 90245

15 November 1980

Final Report

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION UNLIMITED

DDC FILE COPY

Prepared for
SPACE DIVISION
AIR FORCE SYSTEMS COMMAND
Los Angeles Air Force Station
P.O. Box 92960, Worldway Postal Center
Los Angeles, Calif. 90009

DTIC
ELECTE
S JAN 14 1981 D


81 1 14 002

This interim report was submitted by The Aerospace Corporation El Segundo, CA 90245, under Contract No. F04701-80-C-0081 with the Space Division, Deputy for Technology, P.O. Box 92960, Worldway Postal Center, Los Angeles, CA 90009. It was reviewed and approved for The Aerospace Corporation by G. A. Paulikas Director, Space Sciences Laboratory. Lieutenant James C. Garcia, SD/YLXT, was the project officer for Mission-Oriented Investigation and Experimentation (MOIE) Programs.


This report has been reviewed by the Public Affairs Office (PAS) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication. Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.


J. C. Garcia, Lt, USAF
Project Officer


Joseph J. Cox, Jr., Lt Col.
USAF
Chief, Advanced Technology
Division

FOR THE COMMANDER


Burton H. Holaday, Col., USAF
Director, Directorate of Space Systems Planning
Deputy for Technology

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

19 REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER (18) SD-TR-80-77	2. GOVT ACCESSION NO. AD-A093765	3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) (6) VLF EMISSIONS FROM A MODULATED ELECTRON BEAM IN THE AURORAL IONOSPHERE		5. TYPE OF REPORT & PERIOD COVERED (9) Final Report	
7. AUTHOR(s) (10) Robert H. Holzworth and Harry C. Koons		6. PERFORMING ORG. REPORT NUMBER (14) TR-0081(6960-05)-1	
9. PERFORMING ORGANIZATION NAME AND ADDRESS The Aerospace Corporation El Segundo, Calif. 90245		8. CONTRACT OR GRANT NUMBER(s) (15) F04701-80-C-0081	
11. CONTROLLING OFFICE NAME AND ADDRESS Space Division Air Force Systems Command Los Angeles, Calif. 90009		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) (16) 21		12. REPORT DATE 15 November 1980	
		13. NUMBER OF PAGES 19	
		15. SECURITY CLASS. (of this report) Unclassified	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A discrete VLF frequency of 3 kHz was successfully radiated by a modulated electron beam on a rocket launched into an active aurora. Instrumentation on this flight included a programmable electron accelerator on the aft section with various particle and field detectors on the aft section as well as the ejected forward payload. The accelerator programmer included a current modulation period at fixed electron energy for 0.45 seconds duration approximately every 11 seconds throughout the flight. In each of these programs steps 4 kV electrons are current modulated at a 3 kHz rate between $I_{min} = 0$			

00 FORM 1473
(FACSIMILE)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

407512

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

19. KEY WORDS (Continued)

20. ABSTRACT (Continued)

or 10 ma and $I_{\max} \approx 80$ ma. The forward payload, which was ejected at about 10 meters per second, included a pair of spherical double probes separated by 2.75 meters and connected to a VLF receiver operating between 30 Hz and 18 kHz. Both this broadband receiver output as well as various narrow band channel outputs were directly telemetered to ground. Post flight spectrum analysis of the broadband VLF data clearly indicates that signals during the 3-kHz accelerator modulation periods were propagated to the forward payload. A detailed analysis of these modulated pulses detected by the VLF receiver is presented. A time-delay analysis between the start of the modulation and detection at the forward payload indicates time delays up to 0.2 seconds. The electron beam is believed to have produced a beam-plasma discharge making a radiation efficiency calculation difficult. However, absolute received signal strength was about 1 mv/m at 1.4 km separation.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

PREFACE

The authors wish to acknowledge the support of W. Bernstein, the principal investigator for the flight, S. Monson who provided support for the experiment at the range and W. B. Harbridge and C. W. Jordan in constructing and integrating the payload. The spectral data analysis was assisted by M. Dazey, W. B. Harbridge and R. Maulfair.

This work was supported in part by The National Oceanic and Atmospheric Administration under Contract 03-5-022-95 and in part by the Space Division of the U.S. Air Force under Contract F04701-80-C-0081.

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

CONTENTS

PREFACE.....	1
INTRODUCTION.....	7
INSTRUMENTATION.....	8
ENVIRONMENTAL FLIGHT CONDITIONS.....	9
OBSERVATIONS.....	9
DISCUSSION.....	16
REFERENCES.....	19

FIGURES

1.	A 25-second VLF spectrum from 0 to 4 kHz along with 3 individual power time profiles during AMP's on the NASA rocket 27.010AE.....	10
2.	A single spectral sweep during the AMP at 045329.5 UT April 9, 1979.....	12
3.	Time delay analysis between turn on of 3 kHz accelerator modulation and leading edge detection at forward payload in the electric spectrum.....	14
4.	A power-time and spectral study of a single AMP at 045329.5 UT.....	15
5.	Two cases showing timing variations between received AMP signals in the Electric and Magnetic receivers.....	16

Introduction

In an active experiment to study plasma dynamics in the auroral ionosphere, NASA sounding rocket 27.010 AE was launched on April 9, 1978 from Ft. Churchill, Manitoba, Canada. The rocket carried an electron accelerator and a full complement of plasma diagnostic devices including electric and magnetic receivers, particle detectors and photometers. The accelerator was mounted on the aft payload which remained attached to the rocket motor throughout the flight. The diagnostic devices were arranged on various Throw Away Detectors laterally ejected (TAD's) and a forwardly ejected payload. An important experiment performed in this flight which this paper addresses exclusively involved the 3 kHz modulation of the electron beam current at fixed voltage and the subsequent detection of a 3 kHz signal by electric and magnetic receivers on the forward payload at distances up to several kilometers away.

Following ejection of the forward payload at about 10 m/sec and antenna deployment the electron accelerator on the aft payload was operated in a mode in which the current was modulated between $I_{\min} = 0$ to 10 ma and $I_{\max} \approx 80$ ma at 3 kHz for 450 msec every 11 sec. Every one of these accelerator modulation periods (AMP's) were detected by the forward payload in the electric VLF spectrum. In this paper it will be demonstrated that a) the VLF spectrum was sharply peaked at 3 kHz with no significant drifting during AMP's, b) there is a measurable time delay between start of AMP and detection at the forward payload of 1 to 2 tenths of a second, c) that the received AMP's are quite structured in time possibly due to beam plasma discharge phenomena, and d) that the AMP's are also visible in the magnetic spectrum but with time delays which differ from the electric signals.

Instrumentation

The aft payload was equipped with two Machlett EE-65 electron accelerators which injected electron beams at 45° to the spin axis with a half cone angle of about 5° . Partial malfunction of the accelerator programmer caused a variety of spontaneous program variations in flight. However, after a few seconds the accelerator operation settled down and the AMP's appeared relatively reliably throughout the flight. At 4 kV beam energy the maximum current, I_{\max} , was about 80 milliamps. Modulation occurred between I_{\max} and either 10 ma or 0 ma which could not be distinguished following the accelerator program malfunctions. The DC current step operation of the accelerator along with some of the particle observations have been described by Wilhelm et al., 1980. Accelerators have also been flown on auroral zone rockets by Winckler, 1975 and 1976. The other relevant instruments included magnetic and electric VLF receivers and antennas on the forward payload. These wave receivers are similar to ones flown before (Koons and Pongrantz, 1979) and will be briefly described here.

The electric antenna consists of a pair of spherical probes separated by 2.75 meters on rigid booms mounted 1 to the spin axis. The magnetic antenna consists of a ferrite rod with multiple windings mounted inside the forward payload. Following preamps and AGC's both electric and magnetic signals up to 16 kHz were directly telemetered on a wideband channel to ground. The preamps also fed fixed-frequency, narrow-band channel amplifiers with digital telemetry outputs. One of these narrow band filter channels was set at 3 kHz which allowed accurate determination of absolute signal amplitudes for the 3 kHz AMP's. All electronics in these receivers operated perfectly except that

onboard EMI away from our range of interest caused the magnetic AGC to operate in its least sensitive mode throughout the flight. Thus the broad band magnetic spectra are considerably more noisy than the electric.

Environmental Flight Conditions

NASA flight 27.010 AE was launched at 04:51:10 UT April 9, 1978 from Ft. Churchill at 152° azimuth and attained an apogee of 246 km at 255 sec after launch. A brief breakup event had occurred about 1/2 hour prior to launch and a bright arc existed just south of the zenith at launch. Ground photometric measurements indicated an intensity of 70 - 100 kR throughout the flight (Bernstein, private communication, 1978). The rocket entered the center of the bright arc from below, penetrated the equatorward boundary near apogee and remained in a quiet environment the remainder of the flight. D. Evans (private communication, 1978) characterized the precipitated electron flux as intense and energetic with a characteristic energy peak between 14 and 20 keV while the rocket was inside the arc. Thus the AMP's were performed under a variety of auroral conditions.

Observations

Figure 1 shows a 25 second sequence of the electric VLF spectrum from 0 to 4 kHz. In this figure three AMP's are shown as indicated along the top. Below each of these modulation periods are expanded electric amplitude - time profiles of a narrowband filter centered at 3 kHz with a 10 Hz bandwidth. The 60 cycle harmonic bands in the lower portion of the spectrogram are artifacts





Figure 1. A 25-second VLF spectrum from 0 to 4 kHz along with 3 individual power time profiles during AMP's on the NASA rocket 27.010AE.

of the original telemetry recording. At the time of figure 1 the forward payload is about 1400 m away from the electron accelerator on the aft payload. The three amplitude-time profiles also indicate that the received 3 kHz signals are about the same length and not significantly longer than the 0.45 msec AMP. This, and the absence of rising or falling tones suggests that the local plasma was not unstable to nonlinear growth of this particular VLF frequency. Thus, the received power can be attributed solely to that radiated from the beam/plasma environment generated by the accelerator. The magnetic spectrum during this 25 sec period also shows the 3 kHz AMP's but as mentioned above an EMI problem caused the magnetic signal-to-noise to be lower; individual examples from the magnetic spectra will be shown later.

Figure 2 is an example of an individual VLF electric spectrum during an AMP. This demonstrates the discrete nature of the received signal and that the center frequency is indeed 3 kHz and has not drifted measurably. In this figure the 3 kHz pulse width is less than the 1 Hz bandwidth. Using the calibrated 3 kHz digital filter channel the peak AMP electric field strengths were about 1 mv/m.

Careful time delay analysis was performed in which the digital telemetry channel for the accelerator current from the aft payload was used as a timing mark for the beginning of each AMP. The leading edge of significant power increase in the 3 kHz channel from the digital telemetry was also measured. However in many cases the timing of the leading edge of the received signal was ambiguous because of other natural VLF phenomena such as sferics. Eliminating all such ambiguous cases the time delays between start of AMP and onset



045329.50

APRIL 9, 1978

Figure 2. A single spectral sweep during the AHP at 045329.5 UT April 9, 1978. The two low frequency spikes are artifacts of the recording process.

of detection at the forward payload are shown in Figure 3. The gaps in Figure 3 are due to occasional irregularity of occurrence of AMP due to the accelerator programmer troubles as mentioned before or to spheric interference with leading edge or due to extremely low signal to noise. The propagation time for the 3 kHz signal to reach the forward payload is often significantly slower than for an electromagnetic wave which could not be resolved on this time scale. The apparently systematic changes in the time delays shown in this figure suggest that the signals are not simply space charge disturbances emanating from the aft payload. The magnetic spectrum was too noisy to allow this kind of 10 msec timing study in all but a few cases which will be discussed below.

A narrow band filter of 5 Hz was used in Figure 4 on the broadband VLF electric signal at 3 kHz to get a better look at the spiky nature of the received AMP signals. The complicated temporal nature of the received 3 kHz power does not appear to be caused by the slow variation of either the injected pitch angle or the antenna angle to the magnetic field. The electric dipole antenna was oriented nearly to both B and the line from the aft to the forward payloads. Therefore all transverse electromagnetic (e.g., whistler mode, etc.) signals arising from strictly nearby the neighborhood of the accelerator would be seen with maximum efficiency.

The last figure shows a comparison between electric and magnetic VLF spectra at two separate times during the flight. These figures clearly demonstrate that the received electric and magnetic signals are not always coincident in time. In Figure 5a the magnetic signals appears to be slightly delayed from the electric signal but the differing power time profile may be




Figure 3. Time delay analysis between turn on of 3 kHz accelerator modulation and leading edge detection at forward payload in the electric spectrum. Data gaps are due to irregularity of occurrence of AMP's and due to leading edge interference by other VLF phenomena.




Figure 4. A power-time and spectral study of a single AMP at 045329.5 UT. In this figure the spectral sweeps in the middle panel are averages for 0.06 sec or roughly the length of the plotted spectra starting at the indicated arrows.




Figure 5. Two cases showing timing variations between received AMP signals in the Electric and Magnetic receivers. Figure 5a shows E field leading B field signals and Figure 5b shows the opposite later in the flight. Pulses above each spectrum indicate time code.

consistent with the two being coincident. However figure 5b shows just the opposite, namely that the magnetic signal leads the electric signal by about 0.2 sec. These two cases are about 4 minutes apart and 5a occurs inside the bright arc while 5b occurs equatorward of the arc. Also, the two payloads are nearly on the same field line on the up leg but definitely on separate field lines on the down leg.

Discussion

In this experiment we successfully radiated a discrete VLF frequency with an electron beam. The radiation efficiency is difficult to calculate because the beam itself was probably generating a beam plasma discharge (BPD). This plasma physics problem is still under investigation by the 27.010 rocket team. BPD has been reported on rocket flights using similar gun currents and voltages (Galeev et al., 1976; Mishin and Ruzhin, 1978) and in the laboratory under simulated ionospheric conditions (Bernstein et al., 1975; 1979). In a BPD some of the beam energy goes into heating the plasma through the two stream or other instability, but it is not clear just how this would affect the current distribution in space which determines the radiation efficiency. At these energies and currents BPD is ignited in the lab within a few tenths of a millisecond consistent with the 3 kHz modulation rate (Bernstein, private communication, 1980).

The electron accelerator delivered a peak DC power of (4kV) (80 ma) = 320 watts with an injection pitch angle which varied with respect to B between 0 and about 135° as the rocket precessed. Thus the field line would act as several stacked dipole radiators of effective length dependent on electron

energy and injection angle. Furthermore, in this flight the receiving payload was in the near field region for a whistler mode or ion acoustic wave where the distance to the source was less than or the order of a wavelength. Therefore to determine the antenna radiation pattern requires integration over each dipole or simulated aperture which itself is constantly changing. In order to do this with the beam in BPD would require integration over the electron energy spectrum as well.

While this flight was complicated by accelerator program malfunctions and may involve beam-plasma discharge phenomena it has nevertheless been shown that modulated electron beams in the space plasma environment can be used as discrete frequency VLF antennas.

References

- Bernstein, W., H. Leinbach, H. Cohen, P. S. Wilson, T. N. Davis, T. Hallinan, B. Baker, J. Martz, R. Zeimke, and W. Huber, Laboratory observations of RF emissions at ω_{pe} and $(n + 1/2) \omega_{ce}$ in electron beam-plasma and beam-beam interactions, J. Geophys. Res., 80, 4375-4379, 1975.
- Bernstein, W., H. Leinbach, P. J. Kellogg, S. J. Monson and T. Hallinan, Further laboratory measurements of the beam-plasma discharge, J. Geophys. Res., 84, 7271-7278, 1979.
- Galeev, A. A., E. V. Mishin, R. Z. Sagdeev, V. D. Shapiro and I. V. Snevekenko, "Discharge in the region around a rocket following injection of electron beam in the ionosphere," Sov. Phys. Doklady 21, 641, 1976.
- Koons, H. C. and M. B. Pongratz, Ion cyclotron waves generated by an ionospheric barium release, J. Geophys. Res., 84, 533, 1979.
- Mishin, E. V. and Yu Ya Ruzhin, "Beam Plasma Discharge in the ionosphere: Dynamics of the region in rocket environment in ARAKS and Zarnit zaz experiments," Acad. of Sciences USSR, Institute of Terrestrial Magnetism, Ionosphere and Radio Wave Propagation, preprint 21a, Moscow, 1978.
- Wilhelm, K., W. Bernstein and B. A. Wahlen, Study of electric fields parallel to the magnetic lines of force using artificially injected energetic electrons, Geophys. Res. Lett., 7, 117-120, 1980.

LABORATORY OPERATIONS

The Laboratory Operations of The Aerospace Corporation is conducting experimental and theoretical investigations necessary for the evaluation and application of scientific advances to new military concepts and systems. Versatility and flexibility have been developed to a high degree by the laboratory personnel in dealing with the many problems encountered in the nation's rapidly developing space and missile systems. Expertise in the latest scientific developments is vital to the accomplishment of tasks related to these problems. The laboratories that contribute to this research are:

Aerophysics Laboratory: Launch and reentry aerodynamics, heat transfer, reentry physics, chemical kinetics, structural mechanics, flight dynamics, atmospheric pollution, and high-power gas lasers.

Chemistry and Physics Laboratory: Atmospheric reactions and atmospheric optics, chemical reactions in polluted atmospheres, chemical reactions of excited species in rocket plumes, chemical thermodynamics, plasma and laser-induced reactions, laser chemistry, propulsion chemistry, space vacuum and radiation effects on materials, lubrication and surface phenomena, photo-sensitive materials and sensors, high precision laser ranging, and the application of physics and chemistry to problems of law enforcement and biomedicine.

Electronics Research Laboratory: Electromagnetic theory, devices, and propagation phenomena, including plasma electromagnetics; quantum electronics, lasers, and electro-optics; communication sciences, applied electronics, semiconducting, superconducting, and crystal device physics, optical and acoustical imaging; atmospheric pollution; millimeter wave and far-infrared technology.

Materials Sciences Laboratory: Development of new materials; metal matrix composites and new forms of carbon; test and evaluation of graphite and ceramics in reentry; spacecraft materials and electronic components in nuclear weapons environment; application of fracture mechanics to stress corrosion and fatigue-induced fractures in structural metals.

Space Sciences Laboratory: Atmospheric and ionospheric physics, radiation from the atmosphere, density and composition of the atmosphere, aurorae and airglow; magnetospheric physics, cosmic rays, generation and propagation of plasma waves in the magnetosphere; solar physics, studies of solar magnetic fields; space astronomy, x-ray astronomy; the effects of nuclear explosions, magnetic storms, and solar activity on the earth's atmosphere, ionosphere, and magnetosphere; the effects of optical, electromagnetic, and particulate radiations in space on space systems.

THE AEROSPACE CORPORATION
El Segundo, California

DATE
FILMED
— 8